

NOTES:

- 1. INTERPRET DIMENSIONING AND TOLERANCING IAW ASME Y14.5M-1994.
- 2. REMOVE ALL BURRS AND BREAK ALL SHARP EDGES .030 MAX
- 3. ESTIMATED WEIGHT: LB

2		1	
REV.	ECO	ZONE	DESCRIPTION
01			INITIAL RELEASE


2

3

1

4

ITEM NO.	QTY.	PART NUMBER	DESCRIPTION
1	1	1023	LIFT ARM
2	1	6384K45	BEARING, 3/8" ID X 1.125" OD
3	1	101-246538-003	SCREW, SHOULDER, 3/8 X 3/8, ALLOY STEEL
4	1	101-245110-208	SCREW, SH, 10-32 X 1, PLATED

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES: DECIMAL ± .015 ANGULAR ± .5° DO NOT SCALE DRAWING		CONFIDENTIAL INFORMATION CONFIDENTIAL COMMERCIAL INFORMATION DISCLOSURE OF INFORMATION COULD CAUSE SUBSTANTIAL COMPETITIVE HARM. (EXECUTIVE ORDER 12600, 6/23/87 52FR23781) DRAWN BY: J.GRIFFIN CHECKED BY: ENGINEERED BY: J.GRIFFIN		<div>J&T MACHINE 3633 W. SHERMAN PHOENIX, AZ 602-568-8097 email: jimgriffin_123@yahoo.com</div>	
				TITLE: LIFT ARM ASSEMBLY	
				SIZE B	DWG NO/REV LEVEL: 1024
				SCALE: 1:2	SHEET: 1 OF 1